



由 Autodesk 教育版产品制作

由 Autodesk 教育版产品制作

PARTS	MATERIALS	TREATMENT	AMOUNT
A HOUSING	PA66+GF	SPECIFY COLOR	1
B CONTACT	BRASS	GOLD PLATED	2
C CONTACT	BRONZE	GOLD PLATED	3
D SHIM	SILICA GEL	BLACK	1

TOLERANCE .xxx .xx .x x ANGLE ± 1°		TITLE: 18芯接线自锁电插PC(2*3)面板式线插接头 (正方形) 东莞市昌骏电子有限公司	
PART NO: CJ-ZS18DTF-P01		DRAWING NO.: CJ-ZS18DY0003	
SHEET: 1 / 1		SCALE: 1 : 1	
DRAWN: Xie Wenjun		CHECKS: Long Jichang	
DATE: 2022-01-05			

Engagement force	Rated voltage	Rated current	Rated power
≤20N	220V	60A	220W
Disengagement force	Rated current	Rated voltage	Rated power
≥5N	60A	220V	220W
Mechanical lifespan	Insulation resistance	Contact resistance	Operation Temperature
≥500	≥1000MΩ	≤10mΩ	-40° C~105° C
IP rating	Contact resistance	Operation Temperature	
IP65/IP67	≤10mΩ		
Flammability	UL94 V-0		